


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TYRE SIZE | 425/55 R 17 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 129 D ; 140 A8 |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 420 | RIM REC | 13.00 |
| OD (MM) | 894 | ECE | E11-106R-005104 |
| SLR (MM) | 397 | SRI | 425 |
| RC (MM) | 2704 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 65 | 595 | 760 | 945 | 1075 | 1240 | 1410 | 1540 | 1685 | 1850 |
| 50 | 720 | 920 | 1145 | 1300 | 1505 | 1705 | 1860 | 2040 | 2240 |
| 40 | 800 | 1025 | 1275 | 1450 | 1675 | 1900 | 2075 | 2275 | 2500 |
| 30 | 895 | 1150 | 1430 | 1625 | 1875 | 2125 | 2320 | 2545 | 2795 |
| 25 | 940 | 1200 | 1495 | 1700 | 1960 | 2225 | 2430 | 2665 | 2925 |
| 10 | 1070 | 1370 | 1700 | 1935 | 2235 | 2535 | 2765 | 3035 | 3330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.