


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94040544	<b>RC (IN)</b>	248.4
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L ; W 16 A ; W 16 L ; DD 16
<b>OD (IN)</b>	81.7	<b>RIM ALT</b>	DW 18 L ; W 18 L ; W 18 A
<b>SLR (IN)</b>	38.0	<b>ECE</b>	E4-106R-001494

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	35	41	46	52	58
<b>30</b>	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
<b>25</b>	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
<b>20</b>	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330
<b>5 LT</b>	6910	8040	9170	10300	11430	12550	14410	15740	17080	18240	19200
<b>5 HT</b>	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.