


# FL 630 SUPER

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>600/55 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS   |
| <b>VERSION</b>      | HD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 177 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94048946 | <b>RC (IN)</b> | 161.6           |
| <b>SW (IN)</b>  | 24.1     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 52.5     | <b>ECE</b>     | E11-106R-003005 |
| <b>SLR (IN)</b> | 23.8     |                |                 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 15   | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 73    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | 4020 | 4990 | 5960  | 7240  | 8380  | 9660  | 10950 | 11750 | 13040 | 14330 | 15130 | 16090 |
| 30        | 4870 | 6040 | 7210  | 8770  | 10130 | 11690 | 13250 | 14220 | 15780 | 17340 | 18310 | 19480 |
| 25        | 5480 | 6790 | 8100  | 9850  | 11390 | 13140 | 14890 | 15980 | 17740 | 19490 | 20580 | 21890 |
| 20        | 6080 | 7540 | 8990  | 10950 | 12640 | 14580 | 16530 | 17750 | 19700 | 21640 | 22850 | 24300 |
| 15        | 6360 | 7890 | 9410  | 11450 | 12320 | 15270 | 17290 | 18570 | 20600 | 22640 | 23910 | 25430 |
| 5         | 7240 | 8980 | 10720 | 13040 | 15070 | 17380 | 19710 | 21150 | 23470 | 25780 | 27240 | 28970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.