


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 320/85 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 126 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 329 | RIM REC | W 11 |
| OD (MM) | 1357 | RIM ALT | W 9 ; W 10 |
| SLR (MM) | 621 | ECE | E4-106R-000758 |
| RC (MM) | 4081 | SRI | 650 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 935 | 1090 | 1245 | 1395 | 1550 | 1700 |
| 40 | 935 | 1090 | 1245 | 1395 | 1550 | 1700 |
| 30 | 1005 | 1165 | 1330 | 1495 | 1660 | 1820 |
| 10 LT | 1255 | 1460 | 1665 | 1870 | 2075 | 2280 |
| 10 HT | 1005 | 1165 | 1330 | 1495 | 1660 | 1820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.