


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>IF 710/75 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / COSECHADORA DE ALGODÓN
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	184 A8/B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1930	<b>ECE</b>	E11-106R-004899
<b>SLR (MM)</b>	870	<b>SRI</b>	900
<b>RC (MM)</b>	5852		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000
40	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000
30	3760	4335	4915	5590	6165	6840	7610	8190	8960	9630
15 CYC*	5795	6685	7575	8615	9505	10545	11735	12625	13815	14850
10 CYC*	6320	7290	8265	9400	10370	11505	12800	13770	15070	16200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.