

# AW 708

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / ARBETSFORDON / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON / SLÄPVAGN
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	149 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94051250	<b>RC (IN)</b>	100.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	34.4	<b>ECE</b>	E11-106R-004255
<b>SLR (IN)</b>	15.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>65</b>
<b>5 FR</b>	10030
<b>15 FR</b>	8530
<b>20 FR</b>	8020
<b>25 FR</b>	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.