

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>420/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	134 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1398	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (MM)</b>	631	<b>ECE</b>	E11-106R-005830
<b>RC (MM)</b>	4172	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1170	1360	1550	1740	1930	2120
50	1230	1430	1630	1830	2030	2230
40	1280	1490	1700	1910	2120	2325
30	1345	1565	1785	2005	2225	2440
10 LT	1565	1825	2080	2335	2590	2845
10 HT	1345	1565	1785	2005	2225	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.