


FL 630 ULTRA

TIRE SIZE	800/45 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ESPALHADOR / CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	174 D ; 184 A8



DIMENSÕES US STANDARD

CÓDIGO USA	94054831	RC (IN)	166.9
SW (IN)	32.6	RIM REC	AG 28.00
OD (IN)	54.8	RIM ALT	AG 24.00
SLR (IN)	24.3	ECE	E11-106R-004074

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	4310	4920	5520	6870	7800	9020	10230	11170	12250	13450
40	4730	5400	6060	7540	8580	9900	11230	12270	13450	14770
30	5730	6540	7340	9130	10370	11980	13590	14580	16280	17880
25	6350	7240	8130	10120	11510	13290	15080	16470	18050	19840
20	7140	8150	9150	11390	12940	14960	16960	18520	20300	22310
15	7470	8530	9580	11920	13550	15650	17750	19380	21250	23350
5	8510	9710	10900	13570	15420	17820	20220	22070	24190	26590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.