

FLOTATION 648

TIRE SIZE	600/50 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B



ABMESSUNGEN IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1170	ECE	E4-106R-002306
SLR (MM)	510	PR	16
RC (MM)	3501		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.20	2.40	2.60
10 FR	6540	6880	7210
20 FR	5885	6195	6490
30 FR	5230	5505	5770
40 FR	4670	4915	5150
50 FR	4205	4425	4625
10 DW	4635	4880	5110
20 DW	4170	4390	4600
30 DW	3705	3905	4090
40 DW	3310	3485	3650
50 DW	2980	3135	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.