

# EARTHMAX SR 48

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>27.00 R 49</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> |                   |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK  |
| <b>VERSION</b>      | STANDARD COMPOUND |
| <b>TIRE TYPE</b>    | TL                |
| <b>LI/SS</b>        | 223 B             |



## DIMENSIONS IS STANDARD

|                 |           |                    |    |
|-----------------|-----------|--------------------|----|
| <b>OD (MM)</b>  | 2688      | <b>TRA CODE</b>    | E4 |
| <b>SLR (MM)</b> | 1225      | <b>STAR RATING</b> | ★★ |
| <b>RC (MM)</b>  | 8165      |                    |    |
| <b>RIM REC</b>  | 19.50/4.0 |                    |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 20600 | 21800 | 22400 | 23000 | 23600 | 25000 | 25750 | 26500 | 27250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.