


# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/40 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	154 A8/150 B
<b>LI/SS FREE ROLLING</b>	166 A8/ 162 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94006489	<b>RC (IN)</b>	139.3
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-002311
<b>SLR (IN)</b>	20.1	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
<b>5 FR</b>	14550	15480	16360
<b>10 FR</b>	13090	13930	14730
<b>20 FR</b>	11640	12380	13080
<b>25 FR</b>	10390	11060	11680
<b>30 FR</b>	9360	9950	10470
<b>5 DW</b>	10300	10950	11570
<b>10 DW</b>	9260	9840	10420
<b>20 DW</b>	8230	8750	9260
<b>25 DW</b>	7350	7810	8270
<b>30 DW</b>	6610	7030	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.