

EARTHMAX SR 45 M



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 45 M

EARTHMAX SR 45 M is an All Steel radial tyre specially designed for rigid haul trucks. EARTHMAX SR 45 M provides optimum traction and is ideal for operation in long hauls.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø33"	18.00 R 33	TL	E4	**	191 B	13.00/2.5	--	185	505	1870	856	5608	55	CR
	18.00 R 33	TL	E4	***	195 B	13.00/2.5	-	220	505	1870	856	5608	55	STD
	18.00 R 33	TL	E4	**	191 B	13.00/2.5	--	220	505	1870	856	5608	55	STD
	18.00 R 33	TL	E4	***	195 B	13.00/2.5	-	185	505	1870	856	5608	55	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES		
							
							
B	209 kg						

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.D. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	18.00 R 33	TL	E4	**	191 B	13.00/2.5	--	256	505	1870	856	5608	55	HRC
	21.00 R 33	TL	E4	**	200 B	15.00/3.0	--	243	575	2001	918	6113	63	CR
Ø35"	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	333	664	2180	980	6538	70	CR
	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	435	664	2180	980	6538	70	HRC
	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	390	664	2180	980	6538	70	STD

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES		
						
E4						
B						
209 kg						

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026