


# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 20.5 R 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / LOADER / LOW PROFILE<br>DUMP TRUCK   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 186 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94049745 | <b>RIM REC</b>     | 17.00/2.0 |
| <b>OD (IN)</b>  | 61.0     | <b>TRA CODE</b>    | L5        |
| <b>SLR (IN)</b> | 27.8     | <b>STAR RATING</b> | ★         |
| <b>RC (IN)</b>  | 183.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    |
|-----------|-------|-------|-------|-------|-------|
| 5         | 17600 | 18200 | 19300 | 19800 | 20900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.