

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>280/70 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	112 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	282	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	798	<b>RIM ALT</b>	W 8; W 8 L; W 10
<b>SLR (MM)</b>	356	<b>ECE</b>	E4-106R-000633
<b>RC (MM)</b>	2370	<b>SRI</b>	380

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	530	605	695	785	875	965	1045	1120
40	530	605	695	785	875	965	1045	1120
30	565	650	745	840	940	1035	1120	1200
10 LT	710	815	935	1055	1175	1295	1400	1505
10 HT	565	650	745	840	940	1035	1120	1200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.