

AGRIMAX FORCE

TIRE SIZE	IF 710/55 R 30 CFO
UM	US STANDARD
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIONES US STANDARD

CÓDIGO USA	94059904	RC (IN)	181.7
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	60.8	ECE	E11-106R-005716
SLR (IN)	27.0	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4880	5620	6470	7220	8070	8810	9880	10630
FROM 40 TO 25	5370	6180	7120	7940	8870	9690	10860	11700
20	5580	6430	7400	8240	9230	10070	11290	12150
12	5790	6670	7680	8560	9580	10460	11720	12610
5	6810	7850	9040	10070	11260	12300	13780	14840
UPTO 20 CYC	6980	8040	9250	10320	11530	12590	14110	15190
UPTO 10 CYC	8310	9580	11030	12300	13750	15010	16820	18110
UPTO 5 CYC	9120	10500	12100	13490	15080	16470	18450	19860
5 HT	5580	6430	7400	8240	9230	10070	11290	12150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.