


FL 630 ULTRA

TIRE SIZE	560/45 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRIDARE / TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 D ; 163 A8



DIMENSIONER IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1076	ECE	E11-106R-003012
SLR (MM)	490	SRI	525
RC (MM)	3290		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1040	1185	1330	1650	1880	2170	2460	2690	2945	3235
65	1140	1300	1460	1815	2060	2380	2700	2950	3235	3550
50	1380	1575	1765	2195	2495	2885	3270	3570	3915	4300
40	1560	1780	2000	2490	2830	3270	3705	4050	4440	4875
30	1720	1960	2200	2740	3115	3595	4080	4455	4885	5365
25	1800	2055	2305	2865	3255	3760	4265	4660	5110	5610
10	2045	2335	2620	3260	3710	4285	4860	5305	5815	6390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.