

# EARTHMAX SR 22

<b>TIRE SIZE</b>	<b>17.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ГРЕЙДЕР / ПОГРУЗЧИК / БУЛЬДОЗЕР / ПОГРУЗЧИК / БУЛЬДОЗЕР / ГРЕЙДЕР
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 B ; 182 A2



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94052387	<b>RIM REC</b>	14.00/1.5
<b>OD (IN)</b>	53.1	<b>TRA CODE</b>	E2/L2
<b>SLR (IN)</b>	23.2	<b>STAR RATING</b>	★★
<b>RC (IN)</b>	155.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76	80	83	87	91	94
30	9650	10200	10500	11000	11400	12000	--	--	--	--	--
5	--	--	--	--	--	16100	16500	17100	17600	18200	18700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.