


# FL 639

<b>TIRE SIZE</b>	<b>800/40 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D ; 178 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94513420	<b>RC (IN)</b>	143.4
<b>SW (IN)</b>	32.6	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	47.7	<b>ECE</b>	E11-106R-0010830
<b>SLR (IN)</b>	21.2		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
45	3600	4620	5740	6530	7540	8550	9340	10240	11240
40	3960	5070	6300	7160	8280	9390	10250	11240	12350
30	4780	6130	7630	8670	10020	11360	12410	13600	14950
25	5290	6780	8430	9590	11080	12570	13720	15050	16530
20	5970	7650	9510	10820	12500	14170	15490	16970	18650
15	6250	8000	9950	11320	13070	14840	16200	17760	19510
5	7120	9120	11340	12900	14890	16900	18450	20230	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.