

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>240/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	104 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94022014	<b>RC (IN)</b>	85.7
<b>SW (IN)</b>	9.6	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	29.2	<b>RIM ALT</b>	W 8 L ; W 9 L
<b>SLR (IN)</b>	13.2	<b>ECE</b>	E4-106R-000609

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	940	1080	1230	1390	1550	1710	1850	1980
25	940	1080	1230	1390	1550	1710	1850	1980
20	1000	1160	1320	1500	1660	1830	1980	2130
5 LT	1260	1440	1660	1870	2080	2300	2490	2670
5 HT	1000	1160	1320	1500	1660	1830	1980	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.