

# FS 216

**18.4 - 26**

|                     |  |
|---------------------|--|
| <b>UM</b>           | US STANDARD                            |
| <b>CONSTRUCTION</b> | BIAS                                   |
| <b>MACHINERY</b>    | TOMRUK YÜKLEME / YÜKLEYİCİ<br>TAŞIYICI |
| <b>VERSION</b>      | STEEL BELTED                           |
| <b>TIRE TYPE</b>    | TT                                     |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94027996 | <b>RC (IN)</b> | 174.5           |
| <b>SW (IN)</b>  | 18.4     | <b>RIM REC</b> | DW 16 A         |
| <b>OD (IN)</b>  | 58.1     | <b>ECE</b>     | E11-106R-003637 |
| <b>SLR (IN)</b> | 26.9     | <b>PR</b>      | 10              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 30   | 25   |
|-----------|------|------|
| 5         | 7950 | -    |
| 20        | -    | 5680 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.