


AGRIMAX RT 657

| | |
|---------------------|--|
| TYRE SIZE | 650/65 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 163 D ; 166 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94076260 | RC (IN) | 215.9 |
| SW (IN) | 25.4 | RIM REC | DW 20 B |
| OD (IN) | 71.3 | RIM ALT | DW 21 B ; DW 23 B |
| SLR (IN) | 32.7 | ECE | E4-106R-000624 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|-------|-------|-------|-------|-------|
| 40 | 5160 | 6020 | 6780 | 7530 | 8280 | 8930 | 9890 | 10700 |
| 30 | 5420 | 6330 | 7120 | 7900 | 8700 | 9370 | 10390 | 11290 |
| 25 | 5610 | 6550 | 7360 | 8180 | 9010 | 9700 | 10760 | 11680 |
| 20 | 5940 | 6930 | 7790 | 8660 | 9520 | 10270 | 11390 | 12370 |
| 5 LT | 6920 | 8070 | 9080 | 10090 | 11100 | 11960 | 13260 | 14410 |
| 5 HT | 5940 | 6930 | 7790 | 8660 | 9520 | 10270 | 11390 | 12370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.