

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 800/45 - 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 164 A8/160 B |
| LI/SS FREE ROLLING | 177 A8/173 B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 800 | RIM REC | AG 28.00 |
| OD (MM) | 1393 | ECE | E4-106R-002280 |
| SLR (MM) | 631 | PR | 16 |
| RC (MM) | 4185 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.80 | 2.00 | 2.20 |
|------------|------|------|-------|
| 10 FR | 9085 | 9665 | 10220 |
| 20 FR | 8175 | 8700 | 9200 |
| 30 FR | 7270 | 7735 | 8175 |
| 40 FR | 6490 | 6905 | 7300 |
| 50 FR | 5840 | 6215 | 6500 |
| 10 DW | 6225 | 6620 | 7000 |
| 20 DW | 5600 | 5960 | 6300 |
| 30 DW | 4980 | 5300 | 5600 |
| 40 DW | 4445 | 4730 | 5000 |
| 50 DW | 4000 | 4225 | 4500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.