


AGRIMAX TURF RT 333

TIRE SIZE	380/70 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	125 A8 ; 125 B



РАЗМЕРЫ US STANDARD

USA CODE	94068838	RC (IN)	139.3
SW (IN)	15.0	RIM REC	W 12
OD (IN)	46.9	RIM ALT	W 11 ; W 13
SLR (IN)	21.0	ECE	E11-106R-007112

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2010	2340	2660	2990	3320	3640
25	2010	2340	2660	2990	3320	3640
20	2150	2510	2860	3210	3570	3910
5 LT	2690	3140	3580	4020	4460	4890
5 HT	2150	2510	2860	3210	3570	3910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.