

# FLOTATION 648

<b>TIRE SIZE</b>	<b>800/45 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	158 A8/155 B
<b>LI/SS FREE ROLLING</b>	170 A8/167 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94006557	<b>RC (IN)</b>	164.8
<b>SW (IN)</b>	31.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	54.8	<b>ECE</b>	E11-106R-004557
<b>SLR (IN)</b>	24.8	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
<b>5 FR</b>	17210	17870	18520
<b>10 FR</b>	15490	16080	16670
<b>20 FR</b>	13770	14300	14810
<b>25 FR</b>	12290	12760	13230
<b>30 FR</b>	11070	11490	12010
<b>5 DW</b>	12190	12650	13120
<b>10 DW</b>	10970	11390	11810
<b>20 DW</b>	9750	10120	10490
<b>25 DW</b>	8710	9040	9370
<b>30 DW</b>	7840	8130	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.