


AGRIMAX PROCROP

VF 270/95 R 54

UM IS STANDARD

CONSTRUCTION  RADIAL

MACHINERY İLAÇLAMA

VERSION STEEL BELTED

TIRE TYPE TL

157 D



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 280 | RIM REC | W9 |
| OD (MM) | 1900 | ECE | E11-106R-0010175 |
| SLR (MM) | 895 | SRI | 925 |
| RC (MM) | 5830 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|---------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1765 | 1995 | 2220 | 2405 | 2670 | 2820 | 3080 | 3345 | 3570 | 3755 |
| FROM 65 TO 40 | 1940 | 2190 | 2435 | 2640 | 2930 | 3095 | 3385 | 3675 | 3920 | 4125 |
| 30 | 1980 | 2235 | 2485 | 2695 | 2990 | 3160 | 3455 | 3750 | 4000 | 4210 |
| 20 | 2020 | 2275 | 2535 | 2750 | 3050 | 3220 | 3520 | 3820 | 4080 | 4290 |
| 10 | 2135 | 2410 | 2680 | 2910 | 3225 | 3405 | 3725 | 4045 | 4315 | 4540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.