

AGRIMAX RT 855

TIRE SIZE	480/80 R 50
UM	IS STANDARD
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	159 A8/B



DIMENSIONS IS STANDARD

SW (MM)	489	RIM ALT	DW 15 L ; W 15 L
OD (MM)	2036	ECE	E4-106R-001486
SLR (MM)	941	SRI	975
RC (MM)	6183	TRA CODE	R1W
RIM REC	DW 16 L	TREAD DEPTH (MM)	53,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	2060	2365	2715	3065	3415	3765	4070	4375
40	2060	2365	2715	3065	3415	3765	4070	4375
30	2205	2530	2905	3280	3655	4030	4360	4685
10 LT	2760	3170	3640	4110	4575	5045	5455	5865
10 HT	2205	2530	2905	3280	3655	4030	4360	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.