


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | 600/50 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 D ; 156 E |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1172 | ECE | E4-106R-000805 |
| SLR (MM) | 516 | SRI | 550 |
| RC (MM) | 3574 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 70 | 1480 | 1680 | 2040 | 2360 | 2720 | 3080 | 3320 | 3680 | 4000 |
| 65 | 1620 | 1840 | 2235 | 2585 | 2975 | 3370 | 3635 | 4025 | 4375 |
| 50 | 1960 | 2225 | 2705 | 3125 | 3605 | 4080 | 4395 | 4875 | 5295 |
| 40 | 2205 | 2500 | 3035 | 3515 | 4050 | 4585 | 4940 | 5475 | 5950 |
| 25 | 2560 | 2905 | 3530 | 4080 | 4705 | 5325 | 5740 | 6365 | 6915 |
| 10 | 2915 | 3310 | 4020 | 4650 | 5355 | 6065 | 6540 | 7245 | 7875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.