

# AGRIMAX RT 855

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>420/85 R 34</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 147 A8/B  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 438  | <b>RIM REC</b> | W 15 L          |
| <b>OD (MM)</b>  | 1578 | <b>RIM ALT</b> | W 13 ; W 14 L   |
| <b>SLR (MM)</b> | 728  | <b>ECE</b>     | E11-106R-005179 |
| <b>RC (MM)</b>  | 4782 | <b>SRI</b>     | 750             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 50         | 1450 | 1665 | 1910 | 2155 | 2400 | 2645 | 2895 | 3075 |
| 40         | 1450 | 1665 | 1910 | 2155 | 2400 | 2645 | 2895 | 3075 |
| 30         | 1550 | 1780 | 2045 | 2310 | 2575 | 2835 | 3100 | 3295 |
| 10 LT      | 1940 | 2230 | 2560 | 2890 | 3220 | 3550 | 3880 | 4125 |
| 10 HT      | 1550 | 1780 | 2045 | 2310 | 2575 | 2835 | 3100 | 3595 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.