


# AGRIMAX SPARGO SB

<b>TYRE SIZE</b>	<b>VF 270/95 R 54</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STEEL BELTED
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	157 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94512898	<b>RC (IN)</b>	230.0
<b>SW (IN)</b>	11.0	<b>RIM REC</b>	W9
<b>OD (IN)</b>	74.8	<b>ECE</b>	E11-106R-0010833
<b>SLR (IN)</b>	35.2		

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
45	3900	4400	4900	5310	5890	6220	6790	7380	7880	8280
FROM 40 TO 25	4280	4830	5370	5820	6460	6830	7470	8110	8650	9100
20	4370	4930	5480	5950	6600	6970	7620	8270	8820	9290
12	4460	5020	5590	6070	6730	7100	7760	8430	9000	9460
5	4710	5320	5910	6420	7110	7510	8220	8920	9520	10010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.