


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 270/80 R 36 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 134 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94067046 | RC (IN) | 161.0 |
| SW (IN) | 10.8 | RIM REC | W9 |
| OD (IN) | 53.0 | RIM ALT | W8; W10 |
| SLR (IN) | 24.8 | ECE | E11-106R-006758 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|------|------|------|------|------|
| 30 | 1640 | 1920 | 2200 | 2480 | 2770 | 3000 | 3330 | 3510 | 3840 | 4170 | 4440 | 4670 |
| 25 | 1640 | 1920 | 2200 | 2480 | 2770 | 3000 | 3330 | 3510 | 3840 | 4170 | 4440 | 4670 |
| 20 | 1750 | 2060 | 2360 | 2660 | 2950 | 3210 | 3560 | 3760 | 4110 | 4460 | 4760 | 5000 |
| 5 | 2460 | 2880 | 3300 | 3730 | 4140 | 4500 | 4980 | 5260 | 5750 | 6250 | 6670 | 7010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.