

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 700/50 - 26.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊗ BIAS |
| MACHINERY | BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 157 A8/154 B |
| LI/SS FREE ROLLING | 169 A8/165 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94006519 | RC (IN) | 161.4 |
| SW (IN) | 27.6 | RIM REC | 24.00 |
| OD (IN) | 54.1 | ECE | E4-106R-002278 |
| SLR (IN) | 24.4 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22 | 23 | 26 |
|-----------|-------|-------|-------|
| 5 FR | 16090 | 16710 | 17900 |
| 10 FR | 14480 | 15050 | 16110 |
| 20 FR | 12870 | 13370 | 14320 |
| 25 FR | 11500 | 11940 | 12790 |
| 30 FR | 10350 | 10750 | 11350 |
| 5 DW | 11450 | 11880 | 12730 |
| 10 DW | 10310 | 10690 | 11460 |
| 20 DW | 9160 | 9500 | 10180 |
| 25 DW | 8180 | 8490 | 9090 |
| 30 DW | 7360 | 7640 | 8270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.