


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 620/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94514205	<b>RC (IN)</b>	228.1
<b>SW (IN)</b>	24.4	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	76.2	<b>RIM ALT</b>	DW 20 B; DW 23 B
<b>SLR (IN)</b>	33.4	<b>ECE</b>	E11-106R-0011233

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6920	8020	9140	10380	11490	12600	13830
<b>FROM 40 TO 25</b>	7610	8830	10040	11410	12630	13840	15210
20	7760	9010	10240	11640	12870	14120	15510
12	7910	9180	10450	11870	13140	14400	15820
5	8370	9710	11040	12550	13890	15230	16730
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	10650	12360	14060	15970	17680	19390	21300
5 HT	7760	9010	10240	11640	12870	14120	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.