


# AGRIMAX SPARGO SB

TIRE SIZE	VF 270/95 R 36
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR / PULVERIZADOR AGRÍCOLA
VERSÃO	STEEL BELTED
TIRE TYPE	TL
LI/SS	150 D



## DIMENSÕES IS STANDARD

SW (MM)	280	RIM REC	W9
OD (MM)	1441	ECE	E11-106R-0010612
SLR (MM)	664	SRI	700
RC (MM)	4397		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1435	1620	1800	1955	2170	2290	2505	2715	2900	3050
FROM 65 TO 40	1575	1780	1980	2145	2380	2515	2750	2985	3185	3350
30	1610	1815	2020	2190	2430	2565	2805	3045	3250	3420
20	1640	1850	2060	2235	2475	2615	2860	3105	3315	3485
10	1735	1955	2175	2360	2620	2765	3025	3280	3505	3685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.