


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>800/65 R 32 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / COSECHADORA DE ALGODÓN
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8 ; 175 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94031412	<b>RC (IN)</b>	218.5
<b>SW (IN)</b>	32.2	<b>RIM REC</b>	DW 27 B
<b>OD (IN)</b>	73.0	<b>RIM ALT</b>	DW 25 B ; DH 27 B
<b>SLR (IN)</b>	33.0	<b>ECE</b>	E4-106R-001430

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
30	7000	8070	9890	10800	12030	12930	14150	15210
25	7610	8760	10750	11740	13060	14050	15380	16530
20	8150	9380	11510	12570	13980	15050	16460	17690
10 CYC	12550	14460	17740	19380	21560	23190	25370	27280
5 CYC	13690	15770	19340	21130	23510	25300	27680	29760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.