

AW 09

| | |
|---------------------------|---|
| TIRE SIZE | 300/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 120 A8 |
| LI/SS FREE ROLLING | 132 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94037810 | RC (IN) | 99.2 |
| SW (IN) | 11.6 | RIM REC | 9.00 |
| OD (IN) | 33.9 | ECE | E4-106R-000375 |
| SLR (IN) | 14.8 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 41 |
|-----------|------|
| 5 FR | 6170 |
| 15 FR | 5250 |
| 20 FR | 4940 |
| 25 FR | 4410 |
| 5 DW | 4320 |
| 15 DW | 3670 |
| 20 DW | 3460 |
| 25 DW | 3090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.