

# AS 504

**420/55 - 17****UM** IS STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

133 A8

145 A8



## UNDEFINED IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 430  | <b>RIM REC</b> | 13.00           |
| <b>OD (MM)</b>  | 910  | <b>ECE</b>     | E11-106R-003302 |
| <b>SLR (MM)</b> | 407  | <b>PR</b>      | 16              |
| <b>RC (MM)</b>  | 2712 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.50 |
|------------|------|
| 10 FR      | 4060 |
| 25 FR      | 3450 |
| 30 FR      | 3250 |
| 40 FR      | 2900 |
| 10 DW      | 2885 |
| 25 DW      | 2450 |
| 30 DW      | 2305 |
| 40 DW      | 2060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.