

FLOTATION TR 675

| | |
|---------------------------|---|
| TIRE SIZE | 500/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 145 A8/142 B |
| LI/SS FREE ROLLING | 157 A8/154 B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 515 | RIM REC | AG 16.00 |
| OD (MM) | 1181 | RIM ALT | 15.00; 17.00 |
| SLR (MM) | 542 | ECE | E4-106R-002314 |
| RC (MM) | 3604 | PR | 12 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 2.00 | 2.40 |
|------------|------|------|------|
| 10 FR | 4390 | 5195 | 5775 |
| 20 FR | 3950 | 4675 | 5200 |
| 30 FR | 3510 | 4155 | 4620 |
| 40 FR | 3135 | 3710 | 4125 |
| 50 FR | 2820 | 3340 | 3750 |
| 10 DW | 3085 | 3645 | 4060 |
| 20 DW | 2780 | 3280 | 3655 |
| 30 DW | 2470 | 2920 | 3250 |
| 40 DW | 2205 | 2605 | 2900 |
| 50 DW | 1985 | 2345 | 2650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.