


# AGRIMAX RT 600

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>750/70 R 26</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HARVESTER / SPREADER / TRACTOR / IMPLEMENTS  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 172 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94073146 | <b>RC (IN)</b> | 207.4           |
| <b>SW (IN)</b>  | 30.7     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 68.9     | <b>RIM ALT</b> | DW 24 B         |
| <b>SLR (IN)</b> | 30.9     | <b>ECE</b>     | E11-106R-007934 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    | 41    | 46    | 52    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 5970 | 6940  | 7930  | 8900  | 9780  | 10840 | 11950 | 12640 | 13890 | -     | -     |
| 25        | 5970 | 6940  | 7930  | 8900  | 9780  | 10840 | 11950 | 12640 | 13890 | -     | -     |
| 20        | 6400 | 7440  | 8490  | 9520  | 10570 | 11610 | 12800 | 13550 | 14880 | -     | -     |
| 5 LT      | 8010 | 9310  | 10630 | 11930 | 13230 | 14540 | 16030 | 16950 | 18630 | -     | -     |
| 5 HT      | 6400 | 7440  | 8490  | 9520  | 10570 | 11610 | 12800 | 13550 | 14880 | -     | -     |
| 5 CYC     | -    | 11170 | 12730 | 14290 | 15850 | 17420 | 19200 | 20310 | 22320 | 22670 | 23610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.