



US standard



SKID MAX SR 720



PRODUCT DATA SHEET

SKID MAX SR 720



SKID MAX SR 720 (L-4) is an All-Steel radial tire designed for skid steer loaders in the most demanding applications as well as for specialized underground personnel and material transport vehicles. The deep tread (L-4) is made of a special cut-and-chip-resistant compound that provides superior durability in OTR environments. The optimized non-directional block design delivers consistent traction, effective load distribution, and improved machine stability across highly abrasive and variable ground conditions. SKID MAX SR 720 (L-4) features an All-Steel casing combined with a reinforced sidewall, delivering superior structural strength and increased resistance to external impacts. This construction ensures reliable performance under high load and torque conditions typical of heavy-duty operations in the harshest environments.



Radial



Technologies



All Steel



Special Antistatic Compound

Performance



Cut Resistance



Durability



Comfort



Stability

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 16.5"	94520749	260/70 R 16.5 (10 R 16.5)	TL	-	141 A2	CRC	L-4	-	30.6	10.4	14.1	93.4	39	88	8.25	7.50 ; 9.00
	94520190	300/70 R 16.5 (12 R 16.5)	TL	-	147 A2	CRC	L-4	-	32.8	12.4	15.0	100.0	43	112	9.75	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment. All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.