


RT 747 AGRO INDUSTRIAL

TIRE SIZE	460/70 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	159 A8 ; 156 B



DIMENSÕES IS STANDARD

SW (MM)	465	RIM REC	DW 15 L
OD (MM)	1254	RIM ALT	DW 14 L; DW 16 L
SLR (MM)	556	ECE	E11-106R-005105
RC (MM)	3840	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
50	1535	1890	2245	2560	2915	3265	3505	4000
40	1705	2100	2495	2845	3240	3630	3895	4375
30	1775	2185	2595	2960	3370	3775	4050	4550
25	1805	2225	2645	3015	3435	3850	4130	4640
10 CYC	2560	3150	3745	4270	4860	5445	5845	6565
STATIC	3920	4830	5740	6545	7450	8350	8960	10065

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.