

# TR 678 IND

**600/40 - 22.5**

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| <b>UM</b>           | US STANDARD                                                    |
| <b>CONSTRUCTION</b> | BIAS                                                           |
| <b>MACHINERY</b>    | UYGULAMALI MAKINE / RÖMORK /<br>UYGULAMALI MAKINE / EKSKAVATÖR |
| <b>VERSION</b>      | DUAL BEAD                                                      |
| <b>TIRE TYPE</b>    | TL                                                             |
|                     | 157 A8                                                         |
|                     | 169 A8                                                         |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94065301 | <b>RC (IN)</b> | 128.5           |
| <b>SW (IN)</b>  | 24.2     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 42.7     | <b>ECE</b>     | E11-106R-006973 |
| <b>SLR (IN)</b> | 19.0     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 60    |
|-----------|-------|
| 25 FR     | 12790 |
| 25 DW     | 9090  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.