DATA SHEET

PRINTED ON
22-04-2026

EARTHMAX SR 22

TIRE SIZE	**17.5 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	GRADER / LOADER / DOZER / LOADER / DOZER / GRADER
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	167 B ; 182 A2

DIMENSIONS US STANDARD

USA CODE	94052387	**RIM REC**	14.00/1.5
OD (IN)	53.1	**TRA CODE**	E2/L2
SLR (IN)	23.2	**STAR RATING**	★★
RC (IN)	155.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76	80	83	87	91	94
30	9650	10200	10500	11000	11400	12000	--	--	--	--	--
5	--	--	--	--	--	16100	16500	17100	17600	18200	18700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..