

EARTHMAX SR 431



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 431

EARTHMAX SR 431 (E-4) is an All Steel tyre specially designed for rigid haul trucks operating in severe mining conditions (surface and underground mines). The non-directional tread pattern ensures excellent traction and stability. The tyre features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	16.00 R 25	TL	E4	**	-	11.25/2.0	-	0	452	1532	713	4649	45	CRC UMS
	18.00 R 25	TL	SH4	****	-	13.00/2.5	-	0	520	1660	760	5040	49	CR
	18.00 R 25	TL	E4	**	185 B	13.00/2.5	-	140	520	1660	760	5040	49	CR
	16.00 R 25	TL	E4	**	177 B	11.25/2.0	-	166	452	1532	713	4649	45	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES			
						
						

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.D. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
16.00 R 25	TL	E4	***	183 B	11.25/2.0	-	166	452	1532	713	4649	45	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES			
						
						
B	185 kg					

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026