


AGRIMAX RT 600

IF 1250/50 R 32

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STEEL BELTED
TIRE TYPE	TL
	201 B



UNDEFINED US STANDARD

USA CODE	94068876	RC (IN)	241.6
SW (IN)	49.1	RIM REC	DH44B/1.3 (multi-piece)
OD (IN)	81.2	ECE	E11-106R-006958
SLR (IN)	35.3		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	14380	16300	20460	22700	25250	27170	29730	31970	---	---
25	15690	17780	22310	24750	27530	29620	32140	34840	---	---
20	16790	19020	23870	26480	29460	31700	34690	37290	---	---
5 LT	21020	23820	29890	33160	36890	39690	43430	46690	---	---
5 HT	16790	18020	23870	26480	29460	31700	34690	37290	---	---
UPTO 5 CYC WITH FRONT LOADER	---	26370	33770	37020	42950	47100	51540	55980	56880	59230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.