


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>650/75 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ERNTemaschine / STREUMaschine / TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	172 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	655	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1789	<b>RIM ALT</b>	DW 20 B ; DW 23 B
<b>SLR (MM)</b>	807	<b>ECE</b>	E11-106R-004755
<b>RC (MM)</b>	5416	<b>SRI</b>	850

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2900	3340	4095	4475	4915	5355	5800	6300	-	-
40	2900	3340	4095	4475	4915	5355	5800	6300	-	-
30	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 LT	3885	4480	5490	6000	6590	7180	7770	8445	-	-
10 HT	3105	3575	4385	4790	5265	5735	6210	6745	-	-
10 CYC.	-	4770	6105	6695	7765	8515	9320	10125	10285	10710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.