

AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 24X8.50 - 12 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 81 A8 |
| LI/SS FREE ROLLING | 94 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 216 | RIM REC | 7 JA; 7.00 I |
| OD (MM) | 610 | ECE | E11-106R-0010452 |
| SLR (MM) | 284 | PR | 6 |
| RC (MM) | 1761 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.30 |
|------------|------|
| 10 FR | 940 |
| 25 FR | 795 |
| 30 FR | 750 |
| 40 FR | 670 |
| 10 DW | 645 |
| 25 DW | 550 |
| 30 DW | 515 |
| 40 DW | 462 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.