

AS 504

TIRE SIZE	12.5/80 - 18
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	308	RIM REC	W 9
OD (MM)	987	RIM ALT	9; 11
SLR (MM)	438	ECE	E11-106R-004347
RC (MM)	2892	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.90
10 FR	4410
25 FR	3750
30 FR	3530
40 FR	3150
10 DW	3050
25 DW	2595
30 DW	2440
40 DW	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.