

# AGRIMAX FORCE

TIRE SIZE	IF 710/60 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	170 D



## РАЗМЕРЫ IS STANDARD

SW (MM)	708	RIM REC	DW 25 B
OD (MM)	1716	ECE	E4-106R-001485
SLR (MM)	763	SRI	825
RC (MM)	5126	TRA CODE	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2510	2890	3330	3710	4145	4530	5075	5460
FROM 65 TO 40	2760	3180	3660	4080	4560	4980	5580	6000
30	2870	3305	3805	4240	4740	5175	5800	6240
20	2980	3430	3950	4405	4920	5375	6025	6420
10	3505	4035	4645	5180	5790	6320	7085	7625
UPTO 30 CYC	3585	4130	4755	5300	5925	6470	7250	7800
UPTO 15 CYC	4275	4925	5670	6320	7065	7715	8645	9300
UPTO 10 CYC	4690	5405	6220	6935	7750	8465	9485	10200
10 HT	2870	3305	3805	4240	4740	5175	5800	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.