

# AS 505

<b>TIRE SIZE</b>	<b>6.5/80 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / REBOQUE / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	86 A8
<b>LI/SS FREE ROLLING</b>	98 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	171	<b>RIM REC</b>	5.0
<b>OD (MM)</b>	695	<b>RIM ALT</b>	4½ K; 5 K; 5 J
<b>SLR (MM)</b>	325	<b>ECE</b>	E4-106R-002188
<b>RC (MM)</b>	2106	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	1050
25 FR	895
30 FR	840
40 FR	750
10 DW	740
25 DW	630
30 DW	595
40 DW	530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.