


# EARTHMAX SR 22

<b>TIRE SIZE</b>	<b>23.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTOLIVELLATRICE / PALA CARICATRICE / DOZER / PALA CARICATRICE / DOZER / MOTOLIVELLATRICE
<b>VERSIONE</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 A8 ; 195 A2



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94062911	<b>RIM REC</b>	19.50/2.5
<b>OD (IN)</b>	63.5	<b>TRA CODE</b>	G2/L2
<b>SLR (IN)</b>	27.9	<b>STAR RATING</b>	★
<b>RC (IN)</b>	191.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-
5	-	-	-	-	-	-	-	-	22700	23400	24700	25400	26800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.